



### ORDERING INFORMATION

	CODE	DESCRIPTION	LENGHT
SC	OT9-06 15U	PigTail Fiber 09/125 SC/UPC Simplex 1.5M/0,9 mm	1.5 Mts
	OT9-06 30U	PigTail Fiber 09/125 SC/UPC Simplex 3.0M/0,9 mm	3 Mts
LC	OT9-11 15U	PigTail Fiber 09/125 LC/UPC Simplex 1.5M/0,9 mm	1.5 Mts
	OT9-11 30U	PigTail Fiber 09/125 LC/UPC Simplex 3.0M/0,9 mm	3 Mts

### SPECIFICATION

Fiber Type	SM G657
Jacket Materials	PVC
Connector Type	SC/LC
Ferrule Materials	CERAMIC
Testing Wavelengths	1310+-30/1550+-30NM
Insertion Loss (dB) TIA/EIA-455-117	<0.3dB (PC/UPCV/APC)
Return Loss (dB) TIA/EIA-455-117	>45dB (PC/UPC) >55dB (APC)
Exchangeable	<0.2dB
Operating Temperature	-10 +70
Storage Temperature	-40 +85

### APPLICATIONS

FTTH access network / Telecommunication Networks / CATV Networks /Data communications Networks / Local Area Networks



STREET



HOSPITAL



INDUSTRIES



FTTH



OTHERS