

## DESCRIPTION

OSCH-144 has 6 fiber cable in-out round ports for the cable diameter  $\Phi 13\text{-}\Phi 15\text{mm}$  entry. It is widely applied to the splicing and distributing variable optical cables.

It is made of high-quality ABS plastic and with the mechanical seal structure filled with the seal material. The external component and fastening piece are all made of the high-quality steel. It can be opened after sealing and can be reused without changing sealing material, with silicone rubber insulation tape.



## SPECIFICATION:

- Dimension (mm) 466.5x179.8x120.6
- Weight (Kg) 2.7
- Cable diameter  $\Phi 13\text{-}\Phi 15$
- cable entry ports 3 in 3 out
- Max Capacity of splice tray 6
- Max Capacity 144
- Sealing structure silicon gum material or sticky
- IP Protection Level: IP 65

## ACCESSORIES:

- Splice protector sleeve
- Silicon gum material
- Sticky cincture
- Cable ties
- Sealing washer
- Allen wrench
- Insulated rubber belt

## SPECIFICATIONS

MODEL	MAX.CAPACITY	DIMENSION	MATERIAL	SPLICE TRAY
OSCH-144	144	466.5x179.8x120.6	ABS	6PCS

## APPLICATIONS

FTTH access network / Telecommunication Networks / CATV Networks / Data communications Networks / Local Area Networks




STREET



HOSPITAL



INDUSTRIES



FTTH



OTHERS