

The OFT-PGGXX preforms are made up of 5 powerful helical ASTM A36 steel wires to evenly distribute the gripping force and tension, their anti-corrosion process is based on the ASTM 123 hot-dip galvanized standard.

The OFT-PGGXX is designed for the perfect anchoring of ADSS cables in the deployment of FTTX networks.

5 WIRES - 100Meters					
PART NUMBER	FROM	UP TO	WIRES	LENGTH	UNIT
OFT-PGG 087	8.6	9.6	5 x 2.5mm	700	milimeter
OFT-PGG 087-1	8.0	9.0	5 x 2.5mm	700	milimeter
OFT-PGG 097	9.6	10.6	5 x 2.5 mm	700	milimeter
OFT-PGG 107	10.6	11.6	5 x 2.5 mm	700	milimeter
OFT-PGG 117	11.1	12	5 x 2.5 mm	700	milimeter
OFT-PGG 127	12.1	13	5 x 2.5 mm	700	milimeter
OFT-PGG 137	13.1	14	5 x 2.5 mm	700	milimeter
OFT-PGG 147	14.1	15	5 x 2.5 mm	700	milimeter
5 WIRES - 150Meters					
PART NUMBER	FROM	UP TO	WIRES	LENGTH	UNIT
OFT-PGG 089	8.6	9.6	5 x 2.5mm	900	milimeter
OFT-PGG 099	9.6	10.6	5 x 2.5 mm	900	milimeter
OFT-PGG 109	10.6	11.6	5 x 2.5 mm	900	milimeter
OFT-PGG 119	11.1	12	5 x 2.5 mm	900	milimeter
OFT-PGG 119-2	11.6	12.8	5 x 2.5 mm	900	milimeter
OFT-PGG 129	12.1	13	5 x 2.5 mm	900	milimeter
OFT-PGG 139	13.1	14	5 x 2.5 mm	900	milimeter
OFT-PGG 149	14.1	15	5 x 2.5 mm	900	milimeter

TECHNICAL SPECIFICATION.

- Material Steel ASTM A36.
- Manufacturing standard ASTM 123.
- Interior coating non-slip triangular granite.
- Increased internal diameter.
- Wires Format saves memory.
- For use without a cable guard.
- Shelf life 30 years.
- Humidity relative less than 85%.
- Storage conditions warehouse aeration drying.

