



SC/APC

- OSP9-06102A** Optical SPLITTER 1*2 Single Mode SC connector/APC - 01meter
- OSP9-06104A** Optical SPLITTER 1*4 Single Mode SC connector/APC - 01meter
- OSP9-06108A** Optical SPLITTER 1*8 Single Mode SC connector/APC - 01meter
- OSP9-06116A** Optical SPLITTER 1*16 Single Mode SC connector/APC - 01meter
- OSP9-06132A** Optical SPLITTER 1*32 Single Mode SC connector/APC - 01meter

Y:

Y= 1 – 1 Cable In

XX:

XX=06 – SC Connector

ZZ:

ZZ= 02 – 2 Cable Out

ZZ= 04 – 4 Cable Out

ZZ= 08 – 8 Cable Out

ZZ= 16 – 16 Cable Out

ZZ= 32 – 32 Cable Out

K:

K= A – APC

K= U - UPC

Parameter	Unit	1X2	1X4	1X8	1X16	1X32	
Operating wavelength	nm	1260 – 1650					
Insertion Loss Standard Version*	dB	≤ 4.0	≤ 0.76	≤ 10.5	≤ 13.9	≤ 17.2	
Uniformity Standard Version*	dB	≤ 0.8	≤ 0.8	≤ 1.0	≤ 1.5	≤ 1.8	
Insertion Loss Premium Version*	dB	≤ 3.8	≤ 7.3	≤ 10.2	≤ 13.5	≤ 16.5	
Uniformity premium Version*	dB	≤ 0.8	≤ 0.5	≤ 0.7	≤ 1.1	≤ 1.4	
PDL*	dB	≤ 0.15	≤ 0.3				
Return Loss*	dB	≥ 55					
Directivity	dB	≥ 55					
Operating Temperature	°C	- 40 to + 85					

* Without Connector Loss



STREET



HOSPITAL



INDUSTRIES



FTTH



OTHERS