

Plug-and-Play for ease of use

150 Mbps high-gain wireless network adapter

W311MA Plug-and-Play



Configuration free

Powered by a chip supporting Plug-and-Play, it is automatically installed as soon as being connected without a driver from a CD-ROM or the internet, enabling you to set up a wireless internet connection more easily.



High-gain omnidirectional antenna for better signal stability

It features an external high-gain omnidirectional antenna adjustable to signals for a longer transmission/reception distance and better signal stability, ensuring excellent gaming, movie, and music experience.

Compatible with various types of OS

It is applicable to devices running Windows XP, Windows 7, Windows 8, Windows 8.1, or Windows 10.



Product Specification

HARDWARE FEATURES	
Interface	USB2.0
Dimensions (W x D x H)	39.1mm×17.2mm×12.6mm (L x W x H)
Antenna Type	1* external antenna
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Frequency	2.400~2.4835GHz
Signal Rate	11b: Up to 11Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11n: Up to 300Mbps(dynamic)
Transmit Power	<20dBm (EIRP)
Wireless Modes	Station Mode
Wireless Security	64/128-bit WEP, WPA-PSK / WPA2-PSK, WPA / WPA2
Channel	1~13
OTHERS	
Package Contents	Wireless Adapter W311MA, QIG
System Requirements	windows10 (32/64bits), Windows 8.1(32/64bits), Windows 8(32/64bits), Windows7(32/64bits), Windows Vista(32/64bits), Windows XP(32/64bits)
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉)
	Storage Temperature: -40℃~70℃ (-40℉~158℉)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Related Products	F3、FH456、A9

Shenzhen Tenda Technology Co., Ltd. 6-8 Floor, Tower E3, No. 1001,
Zhongshanyuan Road, Nanshan District,
Shenzhen, China. 518052
Tel: (86 755) 2765 7180 Fax: (86 755) 2765 7178
Email: sales@tenda.com.cn support@tenda.com.cn
Website: <http://www.tendacn.com>