



STRUCTURE DESCRIPTION

1. Loose Tube: Thermoplastic material, containing optical fibers and filled with gel.
2. Filler Elements: Thermoplastic rods.
3. Central Strength Member(CSM):Glass fiber reinforced plastic rod (GFRP), Coated with polyethylene For the fiber of 144 cores in more.
4. Longitudinal Water Blocking Material: Water blocking tape.
5. Peripheral Strength Member: Aramid yarn.
6. Ripcord
7. Outer Sheath: Black polyethylene.

ADSS-09G652XXX-SJ100Z-CN,
Optical Fiber Cable with GFRP central strength member for
Outdoor Application - 06 - 144 Fiber

OPTICAL PROPERTIES

Fiber Type	ITU-T Rec. Low Water Peak (LWP) - G652D	
Fiber yarn count	06F/ 12F / 24F / 48F/ 96F/ 144F	
Attenuation coefficient	1310nm	< 0.36 dB/Km
	1550nm	< 0.23 dB/Km
	1625nm	< 0.22 dB/Km
Point discontinuity	≤ 0.05 dB	
Diameter of modal field	Wavelength: 1310nm, 1550nm, 1625nm	
	Nominal range: 9.2mm Tolerance: ± 0.4mm	
Cladding diameter (nominal)	125 mm ± 0,5 mm	
Primary coating diameter	245 ± 10 um	
Cut-off wavelength	Max: 1260 nm	
PMD coefficient (Polarization Mode Dispersion)	Max: 0,20 ps/√ km	



ADSS-09G652XXX-SJ100Z-CN

ADSS Optic Cable G652 9/125 –
Single Jacket/ 80 mt Span

TECHNICAL PROPERTIES		
External covering material	HDPE	
Outer jacket color	Black	
Jacket protection	UV resistant	
Internal cable structure - Loose tube	ADSS-09G652006-SJ100Z-CN	(1 buffer with 6 threads)
	ADSS-09G652012-SJ100Z-CN	(2 buffer with 6 threads)
	ADSS-09G652024-SJ100Z-CN	(4 buffer with 6 threads)
	ADSS-09G652048-SJ100Z-CN	(4 buffer with 12 threads)
	ADSS-09G652096-SJ100Z-CN	(8 buffer with 12 threads)
	ADSS-09G652144-SJ100Z-CN	(12 buffer with 12 threads)
Loose tube - Outer diameter (mm)	Loose tube - Diameter	
	ADSS-09G652006-SJ100Z-CN	1.9 ± 0.1 mm
	ADSS-09G652012-SJ100Z-CN	1.9 ± 0.1 mm
	ADSS-09G652024-SJ100Z-CN	1.9 ± 0.1 mm
	ADSS-09G652048-SJ100Z-CN	2.15 ± 0.1 mm
	ADSS-09G652096-SJ100Z-CN	2.15 ± 0.1 mm
Central member structure (CSM)	Glass Fiber Reinforced Plastic rod (GFRP)	
	ADSS-09G652006-SJ100Z-CN	2 ± 0.10 mm
	ADSS-09G652012-SJ100Z-CN	2 ± 0.10 mm
	ADSS-09G652024-SJ100Z-CN	2 ± 0.10 mm
	ADSS-09G652048-SJ100Z-CN	2.3 ± 0.10 mm
	ADSS-09G652096-SJ100Z-CN	3.5 ± 0.10 mm
ADSS-09G652144-SJ100Z-CN	6.4 ± 0.10 mm	
Configuration of the internal cable structure	SZ Braided, Thermoplastic Cylinders	
Outer Sheath	Thickness (mm)	1.8 ± 0.1 mm
Estructura de los tubos	Material	Colors of tubes PTB
Cable Diameter (mm)cable OD	ADSS-09G652006-SJ100Z-CN	9.4 ± .45 mm
	ADSS-09G652012-SJ100Z-CN	9.4 ± .45 mm
	ADSS-09G652024-SJ100Z-CN	9.4 ± .45 mm
	ADSS-09G652048-SJ100Z-CN	10.5 ± .45 mm
	ADSS-09G652096-SJ100Z-CN	11.6 ± .45 mm
	ADSS-09G652144-SJ100Z-CN	14.6 ± .45 mm
Ripcord	2 Nos. below armor	
Water Blocking Material	Core wrapping	Water blocking tape
	Water blocking media	Water Swellable Yarn Over CSM
Color code	TIA 598 D Standard: Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose (Pink), Aqua	



ADSS-09G652XXX-SJ100Z-CN

ADSS Optic Cable G652 9/125 –
Single Jacket/ 100 mt Span

Cable breaking strength(RTS)≥	ADSS-09G652006-SJ100Z-CN	4520N
	ADSS-09G652012-SJ100Z-CN	4520N
	ADSS-09G652024-SJ100Z-CN	4520N
	ADSS-09G652048-SJ100Z-CN	6300N
	ADSS-09G652096-SJ100Z-CN	10328N
	ADSS-09G652144-SJ100Z-CN	11250N
Temperature range (IEC 60794-1-F1)	Operation	-20° to +65°C
	Installed	-20° to +65°C
	Storage and Shipping	-20° to +65°C
Tube filling compound	Water Blocking & Moisture Proof Thyrotrophic gel	
Filler	PP Diameter same as tube	
Water blocking tape	0.28mm thickness	
Working Tension (MAT)	ADSS-09G652006-SJ100Z-CN	1808N
	ADSS-09G652012-SJ100Z-CN	1808N
	ADSS-09G652024-SJ100Z-CN	1808N
	ADSS-09G652048-SJ100Z-CN	2520N
	ADSS-09G652096-SJ100Z-CN	4131N
	ADSS-09G652144-SJ100Z-CN	4500N
Dielectric Strength Members	Aramid Yarns 1670Dtex	
Drum length x Km	ADSS-09G652006-SJ100Z-CN	4 Km ± 5%
	ADSS-09G652012-SJ100Z-CN	4 Km ± 5%
	ADSS-09G652024-SJ100Z-CN	4 Km ± 5%
	ADSS-09G652048-SJ100Z-CN	4 Km ± 5%
	ADSS-09G652096-SJ100Z-CN	3 Km ± 5%
	ADSS-09G652144-SJ100Z-CN	2 Km ± 5%
Cable SPAN	100 Mt. SPAN	
GW/Reel	ADSS-09G652006-SJ100Z-CN	325 Kg
	ADSS-09G652012-SJ100Z-CN	325 Kg
	ADSS-09G652024-SJ100Z-CN	325 Kg
	ADSS-09G652048-SJ100Z-CN	369 Kg
	ADSS-09G652096-SJ100Z-CN	365 Kg
	ADSS-09G652144-SJ100Z-CN	326 Kg

Fiber Box Fiber Connectivity Fiber Cassette Fiber Protection Fiber Patch Panel Fiber Patch Panel Optic Cables Cable Fitting



ADSS-09G652XXX-SJ100Z-CN

ADSS Optic Cable G652 9/125 –
Single Jacket/ 100 mt Span

Climate Condition	No Ice, 25m/s Max Wind Speed	
Repeated bending IEC 60794-1-2-E6	25 Cycle, $r = 20 \times D$, 5 Kg, $D = \text{Cable Diameter}$	
Bending radius IEC 60794-1-E11	Load: 5000 N	Loss change 0.1 dB @ 1550 nm
	Length of cable under load: 50m	No fiber break and no sheath damage.
Crush Test IEC 60794-1-E3	Load: 3000 N/100mm	Loss change 0.1 dB @ 1550 nm
	Load time: ≥ 1 min	No fiber break and no sheath damage.
Impact Test IEC 60794-1-E4	Points of impact: 5	Loss change 0.1 dB @ 1550 nm
	Times of per point: 5	
	Impact energy: 4.5Nm	No fiber break and no sheath damage.
	Radius of hammer head: 12.5mm	
Repeated Bending IEC 60794-1-E6	Impact rate: 2sec/cycle	Loss change 0.1 dB @ 1550 nm
	Bending Dia.: 20 x OD	
	Load: 250N	
	Flexing rate: 3sec/cycle	
Torsion IEC 60794-1-E7	No. of cycle: 30	No water shall have leaked from the opposite end of cable
	Length: 1m	
	Load: 150N	
	Twist rate: 1 min/cycle	
	Twist angle: $\pm 90^\circ$	
Compound Flow IEC 60794-1-E14	No. of cycle: 10	No compound flow
	Sample length: 30 cm	
	Temp: 70°C 2°C	
	Time: 24 hour	

Fiber Color And Binder Color Code: According to EIA/TIA 598D

No.	1	2	3	4	5	6
Color	Blue	Orange	Green	Brown	Gray	White
No.	7	8	9	10	11	12
Color	Red	Black	Yellow	Violet	Pink	Aqua

Cable Fitting | Optic Cables | Optic Tools | Fiber Patch Panel | Fiber Protection | Fiber Cassette | Fiber Connectivity | Fiber Box