

OTBSC-0616AOK

Fiber Optic Termination Box 16 FO April 2022

DESCRIPTION

Is a plastic fiber optic terminal box that load plastic splitter cassette 1x8 or 1x16 for optical fiber splitting and distribution. It support 16 drop cable output and cable entry without cutting. It is used for outdoor wall mounted or pole mounted application

FEATURES

- Material: ABS+UV plastic
- Max. 16 fibers splicing capacity
- Can load 1pc splitter cassette 1x16 or 2pcs splitter cassette 1x8
- Cable ports: 2pcs M20 cable ports for Φ6~11mm cable entry
- 1 oval port support Φ6~18mm cable entry without cutting
- 16pcs 2*3mm drop cable or 3.0mm round cable output ports
- Wall mounting and pole mounting application
- Waterproof, outdoor using, IP65

APPLICATIONS

FTTH access network / Telecommunication Networks / CATV Networks / Data communications Networks / Local Area Networks

SPECIFICATION:

Dimension(mm)	182.5X306.4X115.5	
Material	ABS	
Splitter cassette	2pcs D-1X8 or 1pc D-1X16	
Splicing capacity	16 fibers	
Cable port	2 PG gland + 1 oval + 16 drop cable port	
Application	Outdoor wall mounted or pole mounted	








OTBSC-0616AOK

Fiber Optic Termination Box 16 FO

Instruction:



- 1- Cable entry port
- 2- Cable output port
- 3- Fiber optic splice tray (back side with splicing module)
- 4- Heat protection shrinkable sleeve

ACCESSORIES:

Heat protection shrinkable sleeve	60mm*2.6*1.2	As per using capacity
Cable tie	3*120mm white	6 pcs
Countersunk Screws	C type 4*30 metal	4 pcs
Plastic Expansion Pipe	Ф6mm plastic white	4 pcs
Insulating tape	0.15*17mm 8 yards black	1 roll